

SAFETY DATA SHEET
WATER IN FUEL EMULSIFIER - COVAL

Page: 1

Compilation date: 29/07/2015

Revision date: 15/12/2015

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: WATER IN FUEL EMULSIFIER - COVAL

Product code: T1199

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier

Company name: Coval Aquasolve Ltd
320 Garratt Lane
Earsfield
London
SW18 4EJ

Tel: 01920 871836 (office hours only)

Email: inform@covalaquasolve.co.uk

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: * Eye Dam. 1: H318; Aquatic Chronic 2: H411; Skin Irrit. 2: H315

Most important adverse effects: Causes skin irritation. Causes serious eye damage. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: * H315: Causes skin irritation.

H318: Causes serious eye damage.

H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: * GHS05: Corrosion

GHS09: Environmental



SAFETY DATA SHEET

WATER IN FUEL EMULSIFIER - COVAL

Page: 2

Signal words: Danger

Precautionary statements: * P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P273: Avoid release to the environment.

P280: Wear protective gloves/eye protection.

P302+352: IF ON SKIN: Wash with plenty of water/soap.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER/doctor/first aid.

P501: Dispose of contents/container to hazardous or special waste collection point.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

* Hazardous ingredients:

ALCOHOLS, C9-11, BRANCHED AND LINEAR, ETHOXYLATED

EINECS	CAS	PBT / WEL	CLP Classification	Percent
500-446-0	160901-09-7	-	Eye Dam. 1: H318	50-70%

AMIDES, C8-18 (EVEN NUMBERED) AND C18-UNSATD, N,N-BIS(HYDROXYETHYL) - REACH registered number(s): 01-2119490100-53

931-329-6	68155-07-7	-	Aquatic Chronic 2: H411; Eye Dam. 1: H318; Skin Irrit. 2: H315	30-50%
-----------	------------	---	--	--------

BUTYL GLYCOL - REACH registered number(s): 01-2119475108-36

203-905-0	111-76-2	-	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315	5-10%
-----------	----------	---	---	-------

2,2'-IMINODIETHANOL

203-868-0	111-42-2	-	Acute Tox. 4: H302; STOT RE 2: H373; Skin Irrit. 2: H315; Eye Dam. 1: H318	1-5%
-----------	----------	---	--	------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

[cont...]

SAFETY DATA SHEET

WATER IN FUEL EMULSIFIER - COVAL

Page: 3

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

[cont...]

SAFETY DATA SHEET
WATER IN FUEL EMULSIFIER - COVAL

Page: 4

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient

7.2. Conditions for safe storage, including any incompatibilities ventilation of the area. Avoid the formation or spread of mists in the air.

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Specific end use(s): No data available.

Hazardous ingredients:

BUTYL GLYCOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	25 ppm	50 ppm	-	-

2,2'-IMINODIETHANOL

UK	13 mg/m ³	-	-	-
----	----------------------	---	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Blue

[cont...]

SAFETY DATA SHEET

WATER IN FUEL EMULSIFIER - COVAL

Page: 5

Odour: Barely perceptible odour

Evaporation rate: Negligible

Oxidising: Not applicable.

Solubility in water: Soluble

Also soluble in: Most organic solvents.

Viscosity: Viscous

Boiling point/range°C: >100

Melting point/range°C: <0

Flammability limits %: lower: Not applicable.

upper: Not applicable.

Flash point°C: Not applicable.

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: Not applicable.

Vapour pressure: Not applicable.

Relative density: 0.945

pH: 9.50 typical

VOC g/l: Not applicable.

9.2. Other information

Section 10: Stability and reactivity

10.1. Reactivity

Other information: No data available.

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

10.3. Possibility of hazardous reactions

Chemical stability: Stable under normal conditions.

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

[cont...]

SAFETY DATA SHEET
WATER IN FUEL EMULSIFIER - COVAL

Page: 6

ALCOHOLS, C9-11, BRANCHED AND LINEAR, ETHOXYLATED

DERMAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

AMIDES, C8-18 (EVEN NUMBERED) AND C18-UNSATD, N,N-BIS(HYDROXYETHYL)

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg

BUTYL GLYCOL

IVN	RAT	LD50	307	mg/kg
ORL	MUS	LD50	1230	mg/kg
ORL	RAT	LD50	1746	mg/kg

2,2'-IMINODIETHANOL

IVN	RAT	LD50	778	mg/kg
ORL	MUS	LD50	3300	mg/kg
ORL	RAT	LD50	620	µl/kg
SCU	RAT	LD50	2200	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

[cont...]

SAFETY DATA SHEET
WATER IN FUEL EMULSIFIER - COVAL

Page: 7

Hazardous ingredients:

AMIDES, C8-18 (EVEN NUMBERED) AND C18-UNSATD, N,N-BIS(HYDROXYETHYL)

ALGAE	72H IC50	3.9	mg/l
DAPHNIA	72H ErC50	3.2	mg/l
FISH	96H LC50	2.4	mg/l

BUTYL GLYCOL

ALGAE	72H ErC50	1840	mg/l
DAPHNIA	48H EC50	1550	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	1474	mg/l

12.2. Persistence and degradability

Persistence and degradability: The surfactant(s) contained in this preparation complies (comply) with the Biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents, (or are undergoing testing to obtain a derogation within the terms of the directive). Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Mobility: Readily absorbed into soil. Soluble in water.

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Other adverse effects: * Toxic to aquatic organisms.

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: * UN3082

[cont...]

SAFETY DATA SHEET
WATER IN FUEL EMULSIFIER - COVAL

Page: 8

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(AMIDES, C8-18 (EVEN NUMBERED) AND C18-UNSATD, N,N-BIS
(HYDROXYETHYL))

14.3. Transport hazard class(es)

Transport class: * 9

14.4. Packing group

14.5. Environmental hazards

Packing group: * III

Environmentally hazardous: Yes

Marine pollutant: *Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: * E

Transport category: * 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Specific regulations: Not applicable.

Other information: * This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.
H312: Harmful in contact with skin.
H315: Causes skin irritation.
H318: Causes serious eye damage.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.
H411: Toxic to aquatic life with long lasting effects.

[cont...]

SAFETY DATA SHEET

WATER IN FUEL EMULSIFIER - COVAL

Page: 9

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above produce.